Care Series

Hydraulic Patient Transfer Stretcher



S-H-300



Key Features:

- Centrally controlled brake system
- · Collapsible siderails
- Dual side foot pedals
- · Retractable fifth wheel steering system
- X-Ray compatible backrest
- · Shock absorbing, non-marking bumpers

- · Foley bag holder
- 4" (10 cm) mattress included
- Ergonomic push handles
- Storage area in base for oxygen E-cylinder tank
- Storage tray for patient belongings
- · Permanent IV pole

The Amico Hydraulic Patient Transfer Stretcher (S-H-300) provides caregivers the control they need in the emergency environment. The stretchers can be adjusted to various positions – raising, lowering, Trendelenburg, and reverse Trendelenburg – by actuating the hydraulic pistons. The back section is adjustable through the use of gas springs and the knee gatch can be raised and lowered with an optional manual crank.

The stretcher is made of carbon steel and painted by an electrostatic spray (powder-coat). The base cover is made from injection molded ABS plastic and the locking siderails are made from a combination of steel, aluminum extrusion and plastic parts for increased durability and to facilitate easy cleaning. The back section includes an X-Ray-compatible board.

The stretcher comes complete with an IV pole, bumper wheels and actuator dust covers to protect the hydraulic actuators.

Technical Specifications



Model Number	
Model Number	S-H-300
Overall Dimensions	
Overall Length Overall Width	84.5" (214 cm) 33" (84 cm)
Litter Positioning	
Trendelenburg/Reverse Trendelenburg Maximum Fowler Section Inclination Maximum Knee Section Inclination	14° 75° 35° ± 5
Height Range	
Lowest Highest	24.25" (61.5 cm) 34.5" (88 cm)
Surface Dimensions	
Surface Width Surface Length Surface Thickness	25" (64 cm) 75" (191 cm) 4" (10 cm)
Weight Capacity & Caster Diameter	
Maximum Weight Limit Caster Diameter	550 lbs (250 kg) 8" (20 cm)
Mattress	

Optional Features & Accessories:

- Utility tray
- · Four sided brake
- Overbed tables
- Removable IV pole

Amico Beds Corporation reserves the right to change product specifications without notice.

Warranty: One year parts only.

